

## Overview - Fiber Optics

1. What is optical Fiber
2. How optical fiber is better than coaxial copper cable (i.e. advantages of using optical fibers) - more data carrying capacity (band width, band width is proportional to frequency of carrier wave), more security, least electromagnetic interference (EMI).
3. Principle of working - Total Internal Reflection
4. Explain Total Internal Reflection
5. Composition/structure of optical fiber (discuss three layers core, clad and protective sheath along with materials i.e. glass or plastic)
6. How light propagates through fiber - Explain qualitatively and show with the help of diagram.
7. Define acceptance angle, acceptance cone and numerical aperture. Find their mathematical expression/relation. Give physical significance of each.
8. What is  $\Delta$  - fractional change in refractive index and express numerical aperture in terms of  $\Delta$ .
9. What is mode?
10. Classification of optical fibers :
  - (i) Based on Index Profile of core -Step Index (SI) and Graded Index (GRIN). Plot the respective index profiles.
  - (ii) Based on number of modes - Single Mode Fiber (SMF) and Multimode Fiber (MMF)
11. What is V-no of fiber -  $V = \frac{2\pi a \text{N.A.}}{\lambda}$ , where  $a$  is core radius,  $\lambda$  is wavelength of carrier wave; N.A. is numerical aperture of fiber. Cut off value of V is 2.405, if  $V < 2.405$ , fiber is SMF and if  $V > 2.405$ , fiber is MMF. Note that V-no of fiber is also known as Normalized frequency.
12. Various losses through fiber - absorption, scattering, material, bending, coupling loss etc.
13. Attenuation coefficient  $\alpha = \frac{10}{L} \log_{10} \frac{P_{in}}{P_{out}}$ , where L is length of fiber in km,  $P_{in}$  is input power launched into fiber and  $P_{out}$  is output power from the fiber. Units of  $\alpha$  are dB/km.
14. Joints in optical fibers - (i) Splice - permanent joint to increase the length of fiber - two types: mechanical splice and fusion splice (ii) Connector - semi-permanent/temporary joint to connect fiber with transmitter and/or receiver - can be of two types - mechanical (ferrule type) and extended beam connectors (iii) Coupler: device to split and/or combine optical signal from one port to many ports or many to one.
15. Applications of optical fibers - communication system, sensors.
16. Disadvantages of using optical fibers